

Specification	JIVA KS-7217	JIVA KS-7215
Processor	Intel Pine View D525 1.8 GHz / 1 M Cache CPU (Dual Core)	
System Memory	DDR3 800 MHz, SO-DIMM socket x 1, max 4 GB, default 1 GB	
Storage Device	2.5" SATA HDD or SSD Kit (Optional) or CF Kit (Optional)	
Power Supply	12V DC power adaptor, 80W (Optional 120W when equipp with 2nd LCD LM-8055)	12V DC power adaptor, 60W (Optional 80W when equipp with 2nd LCD LM-8015/8025/8035/8045/8055/TM-8045)
Audio	2W speaker	
OS support	Win 7 / Win XP Pro / POSReady 7 / POSReady 2009 / Linux	
Color	Black	Black / White
<b>Display</b>		
LCD	17" TFT LCD, 1280 x 1024 resolution	15" TFT LCD, 1024 x 768 resolution
Touch Function	Resistive, 5-wire, USB Interface / IR touch, USB Interface	Resistive, 5-wire, USB Interface / IR touch, USB Interface Bezel-free, Resistive touch, USB Interface Bezel-free, PC touch, USB Interface
Brightness Control	By digital push button	
Tilt Adjustment	From 15° to 70°	
<b>Connectivity</b>		
LAN Port	10 / 100 / 1000 Mb	
Parallel Port	Optional	
Serial Port	DB9 x 2, RJ-45 x 2 (Optional RJ-45 to DB9 cable), with 5V / 12V support on COM1 / COM2 / COM3 / COM4	
UPS Port	Yes, battery (Optional)	
Standard USB Port	6	
Proprietary USB Port	1 for side mount options	
Powered USB	1 X 24V via 5.5th gen base (Upgrade to 150W power adaptor when equipped with Powered USB)	
VGA Port	D-SUB 15 pins, with 12V power for Posiflex LCD monitor	
CR Port	1, control 2 CR	
<b>Physical Dimension</b>		
Dimension (W x D x H in mm)	410 X 379.4 X 299	378 X 304 X 364
Weight (N. W. in kg)	11	7.7
<b>Environment</b>		
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH	
<b>Options</b>		
PD-306 / PD-306U	N/A	2 x 20 LCD, default 200 mm pole
PD-309 / PD-309U	2 x 20 LCD, default 200 mm pole	
PD-310 / PD-310U	2 x 20 LCD, rear top mount	
PD-2602 / PD-2602U	N/A	2 x 20 VFD, default 200mm pole
PD-2604 / PD-2604U	2 x 20 VFD, rear top mount	
PD-2605 / PD-2605U	2 x 20 VFD, default 200 mm pole	
PD-76X2	N/A	240 x 64 dot graphics LCD, 200 mm pole
SSD	8 GB minimum	
CF Card	Type I card	
MSR	See security device	
Security Device (SD)	SD-466/SD-466Z: 3 tracks MSR (JIS-II optional) and/or Finger Print Sensor SD-666W: 3 tracks MSR (JIS-II optional) and/or iButton SD-866W: 3 tracks MSR (JIS-II optional) and/or RFID and/or WiFi	
UPS Battery	2300 mAh / 12V	
RAID Function	Support RAID 1 (Disk mirroring)	
2nd LCD Display	12" LM-6101B/LM-2312	15" LM-8015B/8025/8035/8045/TM-8045 12" LM-6101B/LM-2312 10" LM-2310
2nd HDD	Yes	
KP-300W	36 Key plus lock keypad and/or MSR and/or smart card reader	
Certifications		

# JIVA KS-7200 Series

**Advanced Innovative FanFree POS Terminal**  
**Elegant Bezel-Free Design**



Design and Manufacturing In Taiwan by Posiflex Technology Inc.  
\*\* The product information and specifications are subject to change without prior notice.

2012 KS7203C1

## JIVA KS-7200 Series

Posiflex unveils the fanfree JIVA KS-7200 series as an advanced innovative POS terminal. The JIVA KS-7200 series catches people's attention by its streamlined and patent aluminum die casting design, bezel-free touch screen, RAID 1 backup, as well as UPS functions. The bezel-free appearance sparks the shop decoration. Built-in UPS function is embedded on main board developed by Posiflex for power backup. Spill-resistant and anti-dust features allow it to operate silently even in a harsh environment. Besides, the JIVA KS-7200 series supports Intel Pine View Dual Core 1.8 GHz CPU with 15" touch screen in a small footprint. It also supports versatile peripheral options such as MSR, customer pole display, programmable keypad, and a wide range of connectivity to meet numerous applications.

The JIVA KS-7200 series presents innovative features and high performance for retailers who concern about data protection.



### Key Features

- ▶ Resistive or IR touch screen for 17" LCD; Resistive, IR, Bezel-free Resistive, or Bezel-free PC touch screen for 15" LCD
- ▶ 17" LCD 1280 x 1024 (JIVA KS-7217), 15" LCD 1024 x 768 (JIVA KS-7215) resolution
- ▶ Spill-resistant design to prevent careless spill and provide easy cleaning for a wide range of applications
- ▶ Equipped with Intel Pine View Dual Core D525 1.8 GHz CPU and DDR3 memory
- ▶ Fanfree design boasting quiet and anti-dust features
- ▶ Patent aluminum die casting design for efficient cooling
- ▶ RAID 1 support to backup important data (Optional)
- ▶ UPS (Embedded on board developed by Posiflex) support to avoid sudden power loss
- ▶ Patent finger lever "Gear Lock" to adjust the LCD tilt angle from 15° to 70°
- ▶ Push-open cover to protect power switch from accidental shutdown
- ▶ Bottom cable guide design and cover for safety and neat outlook
- ▶ User-friendly mechanism for system upgrade and easy maintenance
- ▶ Shiny diamond black or white front bezel for stunning look (Optional)
- ▶ Generation 6 super slim base stand (Optional)

