

Epson

TM-U325

Printer



- Receipt and validation printing in a compact body
- Quiet, 6.4 lps receipt printing speed
- Handles up to 9 lines of validation
- User-friendly features such as drop-in paper loading and Auto Status Back (ASB) messages
- Connect-It™ interfaces for system compatibility
- Renowned Epson quality, reliability, dependability

Compact and powerful, Epson's TM-U325 combines two printers in one: a speedy, quiet receipt printer and a multi-line validation printer.

Epson's TM-U325 is the ideal choice for environments that want to reap the benefits of both a receipt printer and a validation printer — but want it all in one economical, space-saving printer.

Quick and quiet impact printer

Surprisingly fast, Epson's TM-U325 logic-seeking control device allows receipts to print at 6.4 lines-per-second (16 digits, 16 cpi). Even more surprising, the TM-U325 delivers its printing so quietly, customers won't know it's there.

Packs a punch in small spaces

This powerful, space-saving printer measures 164 x 240 x 136mm (W x D x H) (6.46 x 9.45 x 5.35") and weighs only 2.3 kg (approximately 5.07 lbs). Its efficient design lets you make the best use of limited counter space. Even the AC adapter power source is compact. With the TM-U325 print buffer at 45 bytes, there's practically no limit to the number of downloadable fonts you can use to convey the image you want.

Epson printers define "ease-of-use"

No other company offers as many user-friendly features as Epson.

Drop-in paper loading that allows busy operators to replace paper quickly. An Auto Status Back (ASB) feature monitors printer status in real-time, keeping printer operation moving and users productive.

For total compatibility, just Connect-It™

With Epson's exclusive Connect-It interface options, the TM-U325 is totally compatible with today's best-of-breed and component-based systems. Thanks to this technology, you can choose virtually any system you want or use what you already have.

Epson quality and reliability

When you choose Epson's TM-U325, you can be sure you'll get unsurpassed performance and dependability. Because, like all Epson point-of-sale products, the TM-U325 meets Epson's world-renowned standards for quality and reliability.

Epson TM-U325 Printer

Printer Specifications

General	Print method	9 pin, serial impact dot matrix
	Print font	
	Font	7 x 9/9 x 9
	Column capacity	40 or 42 columns/33 or 35 columns
	Character size	1.24 x 3.1mm [W x H]/1.56 x 3.1mm [W x H]; {0.049 x 0.122"/0.061 x 0.122"}
	Character set	95 Alphanumeric, 32 International, 128 x 8 Graphic
Characters per inch	16 or 17.8 cpi/13.3 or 14.5 cpi	
Printer	Interface	RS-232C, Bi-directional parallel, Connect-It*
	Data buffer	4KB/45 bytes
	Print speed	Approx. 3.5 lps [at 40-column printing]/approx. 6.4 lps [at 16-column printing]
	Paper dimensions	Maximum print lines: 9 lines
	Receipt	76±0.5 x diameter 83mm [2.99±0.02 x diameter 3.27"]
	Validation	135 to 182 x 70 to 182mm [W x L] {5.31 to 7.17 x 2.76 to 7.17"}
	Paper thickness	
	Receipt	0.06 to 0.085mm [0.0024 to 0.0033"]/sheet (total thickness: 0.2mm [0.079"] or less)
	Validation	0.09 to 0.12mm [0.0035 to 0.0047"]/sheet (total thickness: 0.09 to 0.31mm) [0.0035 to 0.012"], [including the thickness of roll paper]
	Copy capability	One original and two copies
	Inked ribbon	ERC-38 [black]
	Ribbon life	3,000,000 characters [black]
	Power supply	AC adapter [included], PS-180 [option]
	Power consumption	Approx. 43W
	D.K.D. function	2 drivers
	Reliability	
	MTBF	180,000 hours
MCBF	49,000,000 lines	
Overall dimensions	164 x 240 x 136mm [W x D x H] {6.46" x 9.45" x 5.35"}	
Mass	Approx. 2.3 kg (5.07 lbs)	
Control Board	EMI standards	FCC class A, CE marking
	Safety standards	UL, CSA

Inch values are approximate.

cpi: characters per 25.4mm (characters per inch)

lps: lines per second

*To find out more about our line of Connect-It interfaces, talk to your Epson Sales Representative.

